



Aqua

Bearing Grease



FEATURES

- Excellent resistance to fresh or salt water
- Resists water wash out
- Greater degree of bearing protection
- Superior adhesion properties
- Excellent corrosion resistance
- Significant load carrying ability
- Reduces wear
- Reduces grease consumption

APPLICATIONS

- Dock Gates
- Industrial Washers
- Lamination Equipment
- Paper Making Equipment
- Pumping Stations
- Separating Tanks
- Sewage Treatment Plants

PROPERTIES

Appearance / Physical State	Solid. Paste.
Color	Amber.
Odor	Hydrocarbon-like.
Melting / Freezing Point	Not available
Boiling Point / Range	640.4 °F (338 °C)
Flash Point	491.0 °F (255.0 °C)
Evaporation Rate	Not available.
Flammability	Not applicable.
Vapor Pressure	Not available.
Vapor Density	Not available.
Auto-Ignition Temperature	> 599 °F (> 315 °C)
Density	>0.91162-<0.91509 g/cm (>7.60747-<7.63643 lbs/gal)
VOC Content	0%
NLGI Grade	2
Thickener Type	Aluminum Complex
Base Oil Type	Mineral Oil
Dropping Point	500°F (260°C)
Viscosity	185-235 cSt @ 40°C
4-Ball Weld Load	400 kg
Timken OK Load	60 lb
Temperature Range	-10°F (-23°C) to 350°F(177°C)
Copper Corrosion	1B
Water Washout	5% max

DIRECTIONS

For use on equipment which is frequently exposed to fresh or salt water. Apply either manually or by a suitable applicator. For best results, bearings should be purged of their previous lubricant before introducing new grease.

HANDLING

Observe good industrial hygiene practices.

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
70514	C70514	14.1 oz / 400 g	cartridge	30	32 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved