Accu-Lube[®] LB-9000 Flood Lubricant Cutting Oil

APPLICATIONS

- General machining, sawing and cuttingFood-grade applications
- Swiss style CNC machining centers
- Milling, drilling and tapping
- Medical device manufacturing

HANDLING

Avoid prolonged exposure. Observe good industrial hygiene practices.

STORAGE

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

Dispose in accordance with all applicable regulations.



PHYSICAL PROPERTIES

Appearance / Physical State Liquid.		
Color	Amber.	
Odor	Mild.	
Flash Point	>399.2°F (>204.0°C)	
Water Solubility	Insoluble.	
Specific Gravity	0.92	
VOC Content	2 % ; 0.19 g/l	

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Color
LB9005	5 gal	pail	1	amber
LB9055	55 gal	drum	1	amber



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved