

TEXPEN® Textile Marker

HANDLING

• Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid inhalation of vapors and spray mists. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

 Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

 Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

FEATURES

- Precision rolling ball, stainless steel tip
- Rubber bulb flow control
- Ergonomically correct marker that enables you to mark at all angles, even upside down

MATERIALS COMPATIBILITY

- Safe on most surfaces
- Surface test should be run to determine compatibility prior to use



PHYSICAL PROPERTIES

Appearance / Physical State Liquid		
Odor	Mild. Sweet. Pungent.	
Flash Point	31.0 °F (-0.6 °C)	
Boiling Point / Range 131 - 316 °F (55 - 157.78 °C)		
Evaporation Rate	> 1 (BuAc = 1)	
Vapor Density	> 1 (Air = 1)	

AVAILABLE IN

Color	Marker Tip	Units/Case	Part #
white	fine, steel	48	13080
black	fine, steel	48	13030
yellow	fine, steel	48	13060

