

UV-Marker

STORAGE

 Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, wellventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

HANDLING

 Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation.

DISPOSAL

• Dispose of contents/container to an approved waste disposal plan

FEATURES

- Applies clear mark barely detectable to the eye
- Excellent for security applications
- Marks on plastic, glass and nonporous surfaces
- Drying Time: 45 seconds to 1 minute



PHYSICAL PROPERTIES

| Appearance / Physical State | Liquid. | |
|-----------------------------|--------------------------------|--|
| Color | Clear. | |
| Odor | Aromatic | |
| Flash Point | 108.0 °F (42.2 °C) | |
| Boiling Point / Range | 318 - 338 °F (158.89 - 170 °C) | |
| VOC Content | 90% ; 809 g/L | |
| Evaporation Rate | < 1 (BuAc = 1) | |
| Vapor Density | > 1 (air = 1) | |
| Prop 65 Warning | YES | |

AVAILABLE IN

| Color | Units/ Case | Marker Tip | Net Contents | Part # |
|-------|----------------|-----------------------|-----------------|--------|
| clear | 48 | medium, felt (#29) | | 91195 |
| Clear | 4 | | 1 gal | 82195 |

