



# SAFETY DATA SHEET

Revision Date 24-May-2017

Revision Number 1

This document complies with the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

### GHS product identifier

**Product Name** BRITE-MARK PAINT MARKER

### Other means of identification

**Part Number** Black (40003, 41003, 84002, 84202), Blue (40001, 41001, 84001, 84201), Brown (40007, 84010), Gold (84051), Green (40004, 41004, 84007, 84207), Light Blue (84008), Orange (40010, 41010, 84005, 84205), Pink (84009), Red (40002, 41002, 84006, 84206), Silver (40016, 84050), Violet (84019), White (40008, 41008, 84003, 84203), Yellow (40006, 41006, 84004, 84204)

**Formula Code** A720M (Black), A788M (Blue), A786M (Brown), A946M (Gold), A789M (Green), A783M (Light Blue), A790M (Orange), A787M (Pink), A791M (Red), A945M (Silver), A785M (Violet), A718M (White), A719M (Yellow)

**UN-Number** UN1263

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Solvent based marker

**Uses advised against** No information available

### Supplier's details

**Initial Supplier**  
ITW Permatex Canada  
1-35 Brownridge Road  
Halton Hills, ON, L7G 0C6  
Canada  
TEL: 1-800-452-5823

**Supplier Address**  
ITW PRO BRANDS  
805 E. Old 56 Highway  
Olathe, KS 66061  
TEL: 1-800-443-9536

### Emergency telephone number

**Emergency Telephone Number** 800-535-5053 Infotrac

## 2. HAZARDS IDENTIFICATION

### Classification

This product is considered hazardous according to the criteria set within the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific Target Organ Systemic Toxicity (Single Exposure)	Category 3
Flammable liquids	Category 3

## Label Elements

### Danger



### Hazard Statements

Causes skin irritation  
 Causes serious eye irritation  
 May cause genetic defects  
 May cause cancer  
 May cause respiratory irritation. May cause drowsiness or dizziness  
 Flammable liquid and vapor.

### Physical and Health Hazards Not Otherwise Classified

Not applicable.

### Precautionary Statements

#### Prevention

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces - No smoking.
- Keep container tightly closed.
- Keep cool.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Wash face, hands and any exposed skin thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Use personal protective equipment as required.

#### General Advice

- If exposed or concerned: Get medical attention/advice
- Specific treatment (see supplemental first aid instructions on this label)

#### Eyes

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

#### Skin

- Wash contaminated clothing before reuse.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

- If skin irritation occurs: Get medical advice/attention.

**Inhalation**

- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**Ingestion**

- None

**Fire**

- In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

**Storage**

- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.

**Disposal**

- Dispose of contents/container to an approved waste disposal plant.

**Other information**

Very toxic to aquatic life with long lasting effects.

70.4204% of the mixture consists of ingredient(s) of unknown toxicity.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
n-Butyl acetate	123-86-4	70.1	-	-
Titanium dioxide	13463-67-7	30.18	-	-
Copper	7440-50-8	19.3	-	-
Aluminum	7429-90-5	13.94	-	-
Carbon black	1333-86-4	11.25	-	-
Isopropyl alcohol	67-63-0	6.97	-	-
Silicon dioxide	7631-86-9	6.92	-	-
Aluminum hydroxide	21645-51-2	5.41	-	-
1,2,4 Trimethylbenzene	95-63-6	1.49	-	-
Zirconium oxide	1314-23-4	0.6	-	-
Toluene	108-88-3	0.34	-	-
Quartz	14808-60-7	0.01	-	-

### 4. FIRST AID MEASURES

**Description of necessary first-aid measures****General Advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.

**Eye Contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.

**Skin Contact**

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**Inhalation**

Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.

**Ingestion**

Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Consult a physician if necessary.

**Protection of First-aiders** Use personal protective equipment. Remove all sources of ignition.

**Most important symptoms/effects, acute and delayed**

**Most Important Symptoms/Effects** No information available.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to Physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media** Carbon dioxide (CO<sub>2</sub>). Foam. Dry chemical.

**Unsuitable Extinguishing Media** Water.

**Specific Hazards Arising from the Chemical** Flammable. Keep product and empty container away from heat and sources of ignition. Risk of ignition.

**Explosion Data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal Precautions** Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Stop leak if you can do it without risk.

**Environmental Precautions**

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Small spillage: Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Large spillage: Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Handling** Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use only in an area containing flame proof equipment. Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**Conditions for safe storage, including any incompatibilities**

**Storage** Keep away from open flames, hot surfaces and sources of ignition. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children. Keep container closed when not in use. Keep away from incompatible materials.

**Incompatible Products** Strong oxidizing agents. Strong reducing agents. Strong alkalis. Strong acids.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
n-Butyl acetate 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Copper 7440-50-8	TWA: 0.2 mg/m <sup>3</sup> fume	TWA: 0.1 mg/m <sup>3</sup> fume TWA: 1 mg/m <sup>3</sup> dust and mist (vacated) TWA: 0.1 mg/m <sup>3</sup> Cu dust, fume, mist	IDLH: 100 mg/m <sup>3</sup> dust, fume and mist TWA: 1 mg/m <sup>3</sup> dust and mist TWA: 0.1 mg/m <sup>3</sup> fume
Aluminum 7429-90-5	TWA: 1 mg/m <sup>3</sup> respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m <sup>3</sup> TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
Silicon dioxide 7631-86-9	10 mg/m <sup>3</sup>	20 mppcf TWA; ((80)/(% SiO <sub>2</sub> ) mg/m <sup>3</sup> )	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m <sup>3</sup> respirable particulate matter	-	-
1,2,4 Trimethylbenzene 95-63-6	TWA: 25 ppm	(vacated) TWA: 25 ppm (vacated) TWA: 125 mg/m <sup>3</sup>	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Zirconium oxide 1314-23-4	STEL: 10 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> Zr	TWA: 5 mg/m <sup>3</sup> Zr (vacated) TWA: 5 mg/m <sup>3</sup> Zr (vacated) STEL: 10 mg/m <sup>3</sup> Zr	IDLH: 25 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> except Zirconium tetrachloride Zr STEL: 10 mg/m <sup>3</sup> Zr
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
Silica 112945-52-5	-	(vacated) TWA: 6 mg/m <sup>3</sup> <1% Crystalline silica TWA: 20 mppcf : (80)/(% SiO <sub>2</sub> ) mg/m <sup>3</sup> TWA	IDLH: 3000 mg/m <sup>3</sup> TWA: 6 mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	30/(%SiO <sub>2</sub> +2) mg/m <sup>3</sup> TWA, Total Dust; 250/(%SiO <sub>2</sub> +5) mppcf TWA, respirable fraction; 10/(%SiO <sub>2</sub> +2) mg/m <sup>3</sup> TWA, respirable TWA: 0.1 mg/m <sup>3</sup> (vacated)	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Stoddard solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m <sup>3</sup>	IDLH: 20000 mg/m <sup>3</sup> Ceiling: 1800 mg/m <sup>3</sup> 15 min TWA: 350 mg/m <sup>3</sup>

*Immediately Dangerous to Life or Health. ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH:*

**Other Exposure Guidelines** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

### Appropriate engineering controls

**Engineering Measures** Showers  
Eyewash stations  
Ventilation systems

### Individual protection measures, such as personal protective equipment

**Eye/Face Protection** Safety glasses with side-shields. If splashes are likely to occur, wear: Chemical splash goggles.

**Skin and Body Protection** Chemical resistant gloves. Risk of contact: Boots. Apron.

**Respiratory Protection** No special protective equipment required. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

**Hygiene Measures** When using, do not eat, drink or smoke. Provide regular cleaning of equipment, work area and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Physical State</b>	Liquid.	<b>Appearance</b>	Opaque, Varies.
<b>Odor</b>	Sweet.	<b>Odor Threshold</b>	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
<b>pH</b>	No data available	None known
<b>Melting Point/Range</b>	No data available	None known
<b>Boiling Point/Boiling Range</b>	122.2 °C / 252 °F	None known
<b>Flash Point</b>	27.2 °C / 81 °F	Tag closed cup
<b>Evaporation rate</b>	< 1 (BuAc = 1)	None known
<b>Flammability (solid, gas)</b>	No data available	None known
<b>Flammability Limits in Air</b>		
upper flammability limit	No data available 7.6	
lower flammability limit	No data available 1.7	
<b>Vapor Pressure</b>	No data available	None known
<b>Vapor Density</b>	No data available	None known
<b>Relative Density</b>	No data available	None known
<b>Specific Gravity</b>	No data available	None known
<b>Water Solubility</b>	Slightly soluble	None known
<b>Solubility in other solvents</b>	No data available	None known
<b>Partition coefficient: n-octanol/water</b>	No data available	None known
<b>Autoignition Temperature</b>	No data available	None known
<b>Decomposition Temperature</b>	No data available	None known
<b>Viscosity</b>	No data available	None known

**Flammable Properties** Flammable liquid. Flammable; may be ignited by heat, sparks or flames.

**Explosive Properties** No data available

**Oxidizing Properties** No data available

### Other information

**VOC Content (%)**

A720M Black: 66.61%  
A786M Brown: 67.78%  
A789M Green: 69.77%  
A787M Pink: 48.62%  
A945M Silver: 71.68%  
A718M White: 47.85%  
A788M Blue: 68.83%

VOC (g/l)	A946M Gold: 59.75%
	A783M Light Blue: 50.34%
	A790M Orange: 65.48%
	A791M Red: 66.17%
	A785M Violet: 76.57%
	A719M Yellow: 68.20%
	A720M Black: 672 g/L
	A786M Brown: 712 g/L
	A789M Green: 725 g/L
	A787M Pink: 637 g/L
	A945M Silver: 714 g/L
	A718M White: 627 g/L
	A788M Blue: 694 g/L
	A946M Gold: 689 g/L
A783M Light Blue: 588 g/L	
A790M Orange: 647 g/L	
A791M Red: 671 g/L	
A791M Red: 671 g/L	
A785M Violet: 771 g/L	
A719M Yellow: 716 g/L	

## 10. STABILITY AND REACTIVITY

<b>Reactivity</b>	No data available.
<b>Chemical stability</b>	Stable under recommended storage conditions.
<b>Possibility of hazardous reactions</b>	None under normal processing.
<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Conditions to avoid</b>	Heat, flames and sparks. Incompatible products.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong reducing agents. Strong alkalis. Strong acids.
<b>Hazardous decomposition products</b>	Carbon oxides. Smoke Soot.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	May cause irritation of respiratory tract. May cause drowsiness and dizziness.
<b>Eye Contact</b>	Irritating to eyes. Causes serious eye irritation.
<b>Skin Contact</b>	Irritating to skin. Causes skin irritation.
<b>Ingestion</b>	Ingestion may cause nausea and vomiting.

#### Numerical measures of toxicity - Product

**Unknown acute toxicity** 70.4204% of the mixture consists of ingredient(s) of unknown toxicity.

*The following values are calculated based on chapter 3.1 of the GHS document:*

<b>LD50 Oral</b>	2419 mg/kg
<b>LD50 Dermal</b>	5753 mg/kg mg/L
<b>dust/mist</b>	29.7 mg/L
<b>Vapor</b>	113 mg/L

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Propylene glycol monomethyl ether acetate	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	5321 mg/m <sup>3</sup>
n-Butyl acetate	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Titanium dioxide	> 10000 mg/kg ( Rat )	-	-
Carbon black	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-

Isopropyl alcohol	= 1870 mg/kg ( Rat )	12800 mg/kg ( Rat ) 12870 mg/kg ( Rabbit )	72.6 mg/L ( Rat ) 4 h
Silicon dioxide	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	>2.2 mg/L ( Rat ) 4 h
Aluminum hydroxide	> 5000 mg/kg ( Rat )	-	-
Petroleum naphtha, light aromatic	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4 Trimethylbenzene	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
Toluene	>5580 mg/kg ( Rat )	8390 mg/kg ( Rabbit )	12.5 mg/L ( Rat ) 4 h
Silica	= 3160 mg/kg ( Rat )	-	-
Quartz	-	-	-

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Respiratory or Skin Sensitization** No information available.  
**Germ Cell Mutagenicity** May cause genetic defects.  
**Carcinogenicity** This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide		Group 2B	-	-
Carbon black	A3	Group 2B	-	X
Isopropyl alcohol		Group 3		X
Silicon dioxide		Group 3		
Toluene	A4	Group 3	-	-
Quartz	A2	Group 1	Known	X

#### ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

#### IARC: (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

#### OSHA: (Occupational Safety & Health Administration)

X - Present

**Reproductive Toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Chronic Toxicity** Avoid repeated exposure.  
**Target Organ Effects** Liver. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood. Lungs. Lymphatic system.  
**Aspiration Hazard** No information available.

## 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a severe marine pollutant according to DOT.

### Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Propylene glycol monomethyl ether acetate 108-65-6		LC50 96 h: = 161 mg/L static (Pimephales promelas)		EC50 48 h: > 500 mg/L (Daphnia magna)
n-Butyl acetate 123-86-4	EC50 72 h: = 674.7 mg/L (Desmodesmus subspicatus)	LC50 96 h: 17 - 19 mg/L flow-through (Pimephales promelas) LC50 96 h: = 100	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h	EC50 24 h: = 72.8 mg/L (Daphnia magna)



		mg/L static (Lepomis macrochirus) LC50 96 h: = 62 mg/L static (Leuciscus idus)	EC50 = 98.9 mg/L 30 min	
Copper 7440-50-8	EC50 96 h: 0.031 - 0.054 mg/L static (Pseudokirchneriella subcapitata) EC50 72 h: 0.0426 - 0.0535 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.0068 - 0.0156 mg/L (Pimephales promelas) LC50 96 h: < 0.3 mg/L static (Pimephales promelas) LC50 96 h: = 0.052 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.112 mg/L flow-through (Poecilia reticulata) LC50 96 h: = 0.2 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.3 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.8 mg/L static (Cyprinus carpio) LC50 96 h: = 1.25 mg/L static (Lepomis macrochirus)	-	EC50 48 h: = 0.03 mg/L Static (Daphnia magna)
Carbon black 1333-86-4				EC50 24 h: > 5600 mg/L (Daphnia magna)
Isopropyl alcohol 67-63-0	EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
Silicon dioxide 7631-86-9	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)
Zinc 7440-66-6	EC50 72 h: 0.09 - 0.125 mg/L static (Pseudokirchneriella subcapitata) EC50 96 h: 0.11 - 0.271 mg/L static (Pseudokirchneriella subcapitata)	LC50 96 h: 0.211 - 0.269 mg/L semi-static (Pimephales promelas) LC50 96 h: 2.16 - 3.05 mg/L flow-through (Pimephales promelas) LC50 96 h: = 0.24 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 0.41 mg/L static (Oncorhynchus mykiss) LC50 96 h: = 0.45 mg/L semi-static (Cyprinus carpio) LC50 96 h: = 0.59 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 2.66 mg/L static (Pimephales promelas) LC50 96 h: = 3.5 mg/L static (Lepomis macrochirus) LC50 96 h: = 30 mg/L (Cyprinus carpio) LC50 96 h: = 7.8 mg/L static (Cyprinus carpio)		EC50 48 h: 0.139 - 0.908 mg/L Static (Daphnia magna)
Petroleum naphtha, light aromatic 64742-95-6		LC50 96 h: = 9.22 mg/L (Oncorhynchus mykiss)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
1,2,4 Trimethylbenzene 95-63-6		LC50 96 h: 7.19 - 8.28 mg/L flow-through (Pimephales promelas)		EC50 48 h: = 6.14 mg/L (Daphnia magna)
Toluene 108-88-3	EC50: 12.5 mg/L Pseudokirchneriella subcapitata 72 h static	LC50: 96 h static <=10 mg/L (Rainbow trout)		LC50 48 h: 7.6 mg/L (Daphnia magna)
Silica 112945-52-5	EC50 72 h: = 440 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h: = 5000 mg/L static (Brachydanio rerio)		EC50 48 h: = 7600 mg/L (Ceriodaphnia dubia)

**Persistence and Degradability**

No information available.

**Bioaccumulation**

Chemical Name	Log Pow
n-Butyl acetate	1.81
Isopropyl alcohol	0.05
1,2,4 Trimethylbenzene	3.63
Toluene	2.7

**Mobility** No information available.

**Other Adverse Effects** No information available.

**13. DISPOSAL CONSIDERATIONS**

**Waste Disposal Methods** Dispose of in accordance with federal, state, and local regulations

**Contaminated Packaging** Do not re-use empty containers.

**US EPA Waste Number** D001  
U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Toluene - 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Component	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3 ( 0.34 )			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
n-Butyl acetate	Toxic
Copper	Toxic
Aluminum	Ignitable powder
Isopropyl alcohol	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN-Number** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Marine Pollutant** This product contains a chemical which is listed as a severe marine pollutant according to DOT.

**Description** UN1263, Paint, 3, III, Marine Pollutant, Limited Quantity  
**Emergency Response Guide Number** 128

**TDG**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263, Paint, 3, III, Marine Pollutant, Limited Quantity

**MEX**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1263, Paint, 3, III, Limited Quantity

**IATA**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 3L  
**Description** UN1263, Paint, 3, III

**IMDG/IMO**

**UN-Number** UN1263  
**Proper Shipping Name** Paint  
**Hazard Class** 3  
**Packing Group** III  
**EmS No.** F-E, S-E  
**Marine Pollutant** Product is a marine pollutant according to the criteria set by IMDG/IMO  
**Description** UN1263, Paint, 3, III, (27.2°C c.c.), Marine Pollutant, Limited Quantity

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Regulations**

**Ozone depleting substances** Not applicable  
**Persistent Organic Pollutants** Not applicable  
**Hazardous Waste** Not applicable

Chemical Name	Basel Convention (Hazardous Wastes)
Copper	Y22
Isopropyl alcohol	Y42
Toluene	Y42

**The Rotterdam Convention (Prior Informed Consent)** Not applicable  
**International Convention for the Prevention of Pollution from Ships (MARPOL)** Not applicable

**International Inventories**

**TSCA** Complies

**Legend**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold

			Values %
Copper	7440-50-8	19.3	1.0
Aluminum	7429-90-5	13.94	1.0
Isopropyl alcohol	67-63-0	6.97	1.0
Zinc	7440-66-6	6.432	1.0
1,2,4 Trimethylbenzene	95-63-6	1.49	1.0
Toluene	108-88-3	0.34	1.0

**SARA 311/312 Hazard Categories**

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate	5000 lb			X
Copper		X	X	
Toluene	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
n-Butyl acetate	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Copper	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Titanium dioxide	13463-67-7	Carcinogen
Carbon black	1333-86-4	Carcinogen
Toluene	108-88-3	Developmental
Quartz	14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
n-Butyl acetate	X	X	X		X
Titanium dioxide	X	X	X		X
Copper	X	X	X	X	X
Aluminum	X	X	X		X
Carbon black	X	X	X	X	X
Isopropyl alcohol	X	X	X		X
Zinc	X	X	X		X
1,2,4 Trimethylbenzene	X	X	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION**

---

<b><u>NFPA</u></b>	<b>Health Hazard 2</b>	<b>Flammability 3</b>	<b>Instability 0</b>	<b>Physical and Chemical Hazards -</b>
<b><u>HMIS</u></b>	<b>Health Hazard 2*</b>	<b>Flammability 3</b>	<b>Physical Hazard 0</b>	<b>Personal Protection X</b>

*\*Indicates a chronic health hazard.*

**Prepared By** Product Stewardship  
23 British American Blvd.  
Latham, NY 12110  
1-800-572-6501

**Issuing Date** 14-Nov-2016  
**Revision Date** 24-May-2017  
**Revision Note** Change to classification.

**General Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**